L-SERIES HARD-MOUNT WASHER-EXTRACTORS FOR ON-PREMISE LAUNDRIES



CONTINENTAL

	L1075	L1125
Capacity lbs (kg)	75 (32)	125 (55)
Cylinder Dinch (mm)	iameter 35.5 (900)	42.5 (1080)
Cylinder Dinch (mm)	epth 20 (500)	23.5 (600)
Cylinder V cu ft (m³)	olume 11.2 (318)	19.4 (550)
Net Weigh lbs (kg)	nt 1314 <i>(</i> 596)	2426 (1100)
Crated We lbs (kg)	eight 1502 (681)	2734 (1240)
Machine V	Vidth 43 (1093)	56 (1422)
Machine I	Depth 46 (1163)	55 (1400)
Machine H	Height 57 (1440)	69 (1745)
Door Oper inch (mm)	ning 21.6 <i>(549)</i>	21.6 (549)
Floor to Doinch (mm)	oor 16.5 <i>(420)</i>	24.4 (620)
inch (mm)		60 x 59 x 77 (1520x1490x1960)
Washing S	Speed 40	34
Spin Spee	e d 510	465
G-force	131	130
Drain Diar inch (mm)	neter 3 (76)	3 (76)
Water Inle inch (mm)	ts 3/4 <i>(</i> 19)	1 (25.4)
Recomme PSI (bar)	nded Wate 7-90 (0.5-6)	r Pressure 7-90 (0.5-6)
Water Flow gal/min (I/m		27 (100)
Motor Pow	ver	3.5

With over 50 years of successful operation in on-premise laundries worldwide, Continental's L-Series Washer-Extractors provide proven durability, performace and energy-efficiency. Available in 75- and 125-pound capacities, L-Series Washers are easy-of-use and program.



In the second

2013 Continental Girbau, Inc. Form No. B-OW-L-SERIES 07/13

L-SERIES HARD-MOUNT WASHER-EXTRACTORS PROVEN DURABILITY, EFFICIENCY AND FLEXIBILITY

Continental L-Series Hard-Mount Washer-Extractors—available in 75- and 125-pound capacities—bring durability, efficiency and flexibility to on-premise laundries looking to maximize productivity, reduce maintenance and cut utilities. L-Series Washer-Extractors offer highly programmable controls, durable construction, energy-efficient technology and industry-leading warranties.

DURABILITY IS IN THE DESIGN

Designed to withstand the rigors of constant use, L-Series Washers feature corrosion-resistant AISI-304 stainless steel inner and outer drums. A sturdy door bar with a heavy, reinforced door hinge protects the door window from outside impacts, and a 360-degree door seal eliminates leaking and resulting maintenance hassles. Dispensers are polypropylene and utilize ethylene-propylene on all flexible ducts and hoses for superior protection against contact with chemicals. L-Series machines also feature a heavy-duty housing and double forsheda water seals to protect bearing assemblies. Engineered using a steel H-frame to effectively transmit vibrations away from the machine to anchor locations, L-Series Washers are constructed to last! No wonder L-Series Washers are backed by an industry-leading ContinentalCare™ warranty!

EFFICIENT PERFORMANCE

L-Series Washers are smartly designed without a sump secured to the outer tub. This drastically cuts the water required for every fill. Moreover, an advanced drive system not only delivers high-performance operation, it heightens energy-efficiency. Finally, the L-Series microprocessor control offers an advanced degree of control for hot and cold water mixing for optimum energy savings.

WATER OPTIONS TO FIT ANY LOAD

L-Series Washers feature double-pressure transmitters to provide two water levels so operators can adjust for both large and small load requirements.

PROGRAMMABLE CONTROLS OFFER FLEXIBILITY

Continental's Premier Microprocessor (PM) Control offers an easy-to-use programming system featuring 99 program selection options. Designed for flexibility, the control offers 20 pre-programmed and 79 user-programmable options. Everything from water temperature, wash action and fill levels, cycle time, delayed start, automatic cycle advance, automatic chemical injection, and extract speed are programmable to properly clean a variety of fabrics. Simultaneously, the control allows for programs designed to cut utility costs, boost production and decrease labor.

EASY TO USE AND MAINTAIN

L-Series Washer-Extractors couldn't be easier to operate. L-Series Washer doors open a full 180 degrees for simple loading and unloading. Attendants simply load, select a program number and press start. A self-cleaning, four-compartment dispenser for powders and liquids makes adding detergents quick and easy. Plus, the machines are available with automatic chemical injection inlets—a feature that ensures a consistent clean and eliminates fabric damage by chemical overuse. Further facilitating ease of use, the control illuminates time remaing until wash completion and a diagnostic readout helps owners pinpoint machine errors and needed maintenance. If service is necessary, an advanced design provides easy access to all moving parts.



3-YR LIMITED PARTS WARRANTY 5-YR KEY COMPONENT WARRANTY

DISTRIBUTED BY:





800-256-1073 www.continentalgirbau.com

2500 State Road 44 • Oshkosh, WI 54904 920-231-8222 • Fax 920-231-4666